



washwell PLATETM

Automatic ELISA Plate Washer





((

Features

- Specially designed Manifold assembly to prevent any scratching on bottom of well
- Auto rinse facility while shut down
- Ability to wash single strip of 8 wells
- User programmable soak time, wash cycles and dispensing volume
- On Board two plate incubator at 37°C with programmable timer

- Continuous aspiration to prevent overflow
- Removable manifold
- Built-in stabilizer
- Auto detection of bottom of well and collision prevention
- Waste bottle full warning with audible alarm

Technical Specifications

Manifold: 8 Way Manifold autoclavable **Dispensing**: Programmable up to 1000 μl

ASPIRATING

Method: Continuous through diaphragm pump while dispensing hence preventing overflow

Residual Volume : $< 2 \mu$ l

Waste Bottle: One (Capacity 2 litres) with audible alarm

Wash Bottle : One (Capacity 2 litres)
Rinse Bottle : One (Capacity 2 litres)

Display: 16 digit alphanumeric fluorescent

Liquid contact materials: Silicon, Stainless Steel, Derline

Memory: 100 open Channels

Washing Method: Plate Wash, Strip Wash, Bottom Wash, Overflow Wash, Rinsing, Priming, Disinfect

Shaking: Multi step shaking

Incubator: For Two ELISA Plates, 37°C **Timer**: Individually Programmable 2 Nos.

Power: 50 Watts / 115 - 240 Volts \pm 10 %, 50/60 Hz. **Dimensions in mm (Ixbxh)**: 330 x 405 x 175 (Approx)

Weight: 6 Kgs.



Manifold



Incubator



Peristaltic Pump

Due to continuous development, specifications are subject to change without prior notice.



An ISO 13485: 2012 Certified Company

ROBONIK (INDIA) PVT. LTD.

Plot No. 3 & 4, MIDC Industrial Area, Morivali, Near Ladi Naka,

Ambernath (W) - 421 501, Thane, INDIA

Tel.: +91 (251) 2689000, Fax: +91 (251) 2689001, National Sales: marketing@robonikindia.com, International Sales: export@robonikindia.com



www.robonik.ir